



### 435-INS PIPE GUIDE

#### GUIDE HARDWARE

- Available Materials: Carbon Steel or Stainless Steel.
- Powder-Coated Finish (Carbon Steel Only) 2 Mil Thickness.
- Slide Pad: Heat Bonded P.T.F.E.
- All Fasteners Grade 2 (Industrial).
- American Made.
- Additional Travel -10" (option).
- See 280-INS and 437-INS For Larger Pipe.

#### INSULATION INSERT

- 360° Asbestos-Free Xonotlite Calcium Silicate - 450 PSI Compressive Strength.
- K-Factor: .61 @ 400 Degrees F.
- Meets ASTM C-533, C-585, C-795, E-72 and E-84, Flame Spread -0-, Smoke Developed -0-.
- All Units Include a Vapor Barrier Jacket Meeting ASTM D-744 and Protection Shield of Galvanized or Stainless Steel.

PIPE SIZE	LOAD		1" Ins.		1.5" Ins.		2" Ins.		3" Ins.	4" Ins.
	Vertical	Lateral	A	B	A	B	A	B		
1/2"	115	115	4.38	6	4.94	7	5.44	9	For Larger Pipe Sizes See 280 Ins.	
3/4"	145	145	4.25	6	4.81	7	5.31	9		
1"	185	185	4.44	6.5	4.63	7	5.44	9.5		
1-1/4"	235	235	4.25	6.5	5	9	5.31	9.5		
1-1/2"	265	265	4.38	7	5	9				
2"	335	335	4.38	8	4.94	9.5				
2-1/2"	405	405	4.38	9						
3"	495	495	4.38	9.5						
"A" & "B" DIMENSIONS + / - 1/8"										
Max. Axial Travel 4" / Max. Lateral Travel + / - 1/8"										

### 435-INS PIPE ALIGNMENT/SLIDE GUIDE FOR SMALL PIPE SIZES



Tri-State Industries, Inc.  
4923 COLUMBIA AVENUE  
HAMMOND, IN 46327  
Ph:219-933-1710 / Fx:219933-1719  
www.tristateindustries.com